
GLAZING MANUAL


Commercial, Residential and Thermally Broken













Copyright

The drawings and design contained within this Technical Manual is the Intellectual property of **CONCEPT ARCHITECTURAL SYSTEMS**. The Technical Manual pages and information contained within may not be copied or distributed without the written permission of **CONCEPT ARCHITECTURAL SYSTEMS**. This Technical Manual is to be returned on the request of **CONCEPT ARCHITECTURAL SYSTEMS**.

CONCEPT ALUMINIUM TERMS AND CONDITIONS

Concept Aluminium & Coating Pty Ltd supplies goods strictly in accordance with its Terms and Conditions. A copy can be viewed on our web site.

Disclaimer

Concept Architectural Systems make every effort to ensure the information contained within this Technical Manual is accurate and correct, although Concept Architectural Systems accepts no responsibility or liability for errors or omissions that may be contained within this manual.

The information contained within this Technical Manual is to be used as a guide only. It is the responsibility of the user of this manual to seek professional advise from a relevant qualified engineer to ensure code compliance and structural adequacy of the proposed system based on the project specification and performance requirements.

Concept Architectural Systems disclaims all liability for any losses incurred or damage suffered by anyone who acts or fails to comply with the Technical contents of this manual.

By using this Technical Manual you accept the above conditions.

Issued to:	 	
CAS contact:.	 	
Data.		



AluRES			
2.1	Comet Sliding Window - Single Glazed Fixed Lite	Page	
2.2	Comet Sliding Window - Double Glazed Fixed Lite	Page	
2.3	Comet Sliding Window - Single Glazed Sash	Page	
2.4	Comet Sliding Window - Double Glazed Sash	Page	
2.5	Residential Sliding Window Door Sash	Page	
2.6	Residential Fixed Lite (Comet Apollo Titan)	Page	
2.7	Residential Awning Casement Window Standard Sash	Page	
2.8	Vista Sash	Page	
2.9	Titan Entry - Single Glazed	Page	
2.10	Titan Entry - Double Glazed	Page	1
AluCO	MM		
3.1	7635CG - Single Glazed	Page	1
3.2	Center Glazed - 44mm Single Glazed - Captive Wedge	Page	1
3.3	Center Glazed - 44mm Single Glazed - Non Captive Wedge	Page	
3.3	Center Glazed - 44mm Double Glazed	Page	
3.4	Center Glazed - 55mm Double Glazed	Page	
3.5	Front Glazed - Single Glazed	Page	
3.6	Front Glazed - Double Glazed	Page	•
3.7	10350 Flush Glazed	Page	
3.8	10350 Flush Glazed	Page	
3.9	Inline Sash	Page	,
3.10	Hinged and Top Hung Doors	Page	
3.11	Ultramax Awning / Casement Sash	Page	2
3.12	Apartment Doors - Titan, Ultramax & BIF	Page	2
3.13	10755CG 16055CG Thermally Broken	Page	2
3.14	10055CG - 50mm Pocket	Page	2
AluBRE	EAK		
4.1	Hinged and Sliding Thermally Broken Door	Page	2
4.2	Commercial Thermally Broken - Awning Sash	Page	2
4.3	50mm Residential Thermally Broken - Fixed Lite	Page	2
4.4	50mm Residential Thermally Broken - Fixed Lite	Page	2
4.5	50mm Residential Thermally Broken - Awning Sash	Page	:




Manual history

Manual created MARCH 2021
Manual updates MAY 2025




Glazing (A)	Bead (B)	Wedge (C)	Backing (D)
4mm S/G	CSW12	PF0688-4mm	T10 Tape
5mm S/G	CSW12	PF0688-5mm	T10 Tape
6mm S/G	CSW12	PF0687-6mm	T10 Tape



Pocket width: 12.5mm Glazing block: 4mm

Beads:



Applicable Profiles

CSW 1 Head

CSW 2 Sill

Glazing block: N/A

CSW 3 Jamb


CSW 4 Jamb


CSW 5 Mullion

CSW5 Transom



Glazing (A)	Bead (B)	Wedge (C)	Channel (D)	Backing (E)
18mm S/G	CSW12	PF0688-4mm	PF0830	T10 Tape






Applicable Profiles

CSW1 Head CSW2 Sill CSW3 Jamb CSW4 Mullion CSW5 Transom



Glazing (A)	Channel (B)
4mm S/G	PF0634-4mm
5mm S/G	PF0659-5mm
6mm S/G	PF0553-6.38mm




Pocket width: 8.0mm Glazing block: N/A

Applicable Profiles

CSW 8 Top/ Bottom Rail CSW 6 Lock Stile CSW 7 Interlock Stile



Glazing (A)	Channel (B)	Sash Channel (C)
4mm S/G	PF0634-4mm	PF0634-4mm



CSW8 Rail


Pocket width: 20.0mm Glazing block: N/A

Applicable Profiles

CSW 8 Top/ Bottom Rail CSW 6 Lock Stile CSW7 Interlock Stile



Glazing (A)	Channel (B)	Profiles (C)
4mm S/G	PF0742	Single Glazed
5mm S/G	PF0843	Single Glazed
6mm S/G	PF0636	Single Glazed
8mm - 12mm	Wet Glazing	Double Glazed
18mm S/G	PF0830	Double Glazed



Applicable Systems


Zeus Sliding Window
Ultramax Sliding Window
Comet Sliding Door
Comet Stacker Door

Applicable Profiles

Single Glazed	Double Glazed
CSD4 Rail	DGS81 Rail
DGS92 Wide Lock Stile	DGS98 Wide Lock Stile
CSD5 Lock Stile	DGS96 Lock Stile
CSD6 Interlock	DGS97 Interlock
STK7 4 Panel Interlock	DGS82 Panel Interlock
STK10 3 Panel Adapter	DGS80 3 Panel Adapter
STK4 Interlock	DGS100 UHD Interlock
	DGS101 UHD Meeting Stile



Glazing (A)	Bead (B)	Wedge (C)	Backing (D)
4mm S/G	F56	PF0688-4mm	T10 Tape
5mm S/G	F56	PF0688-5mm	T10 Tape
6mm S/G	F56	PF0687-6mm	T10 Tape
8mm S/G	F65	PF0688-4mm	T10 Tape
10mm S/G	F65	PF0687-6mm	T10 Tape
12mm S/G	F65	PF0518-4mm	T10 Tape
18mm D/G	F55	PF0688-4mm	T10 Tape
20mm D/G	F55	PF0687-6mm	T10 Tape
22mm D/G	F55	PF0518-4mm	T10 Tape
24mm D/G	F64	PF0688-5mm	T10 Tape
24.76mm D/G	F64	PF0687-6mm	T10 Tape




F50 Frame F65 Bead F90 Frame Apollo F91 Frame Titan

Pocket width:

F56 Bead: 13.1mm F65 Bead: 17.0mm F55 Bead: 27.2mm F64 Bead: 31.9mm


Glazing block: 5mm

Beads:





Sash (A)	Glazing (B)	Wedge (C)	Backing (D)
F53-F59	4mm S/G	PF0519-5mm	PX0091
F53-F59	5mm S/G	PF0519-5mm	PX0091
F53-F59	6mm S/G	PF0968	PX0091
F62-F63	8mm- 12mm	Wet Glazing	
F62-F63	18mm S/G	PF0688-4mm	T10 Tape
F62-F63	20mm S/G	PF0688-5mm	T10 Tape
F62-F63	22mm S/G	PF0518-4mm	T10 Tape
F62-F63	24mm S/G	PF0519-6mm	T10 Tape



Applicable Systems


Comet Awning Window Apollo Awning Window Titan Awning Window Apollo Casement Window Titan Casement Window


Applicable Profiles


F53 S/G Sash F59 S/G Hook Sash F62 D/G Sash F63 D/G Hook Sash



Glazing(A)	Bead (B)	Wedge (C)	Backing (D)
5mm S/G	F71	PF0688-4mm	T10 Tape
6mm S/G	F71	PF0688-5mm	T10 Tape
8mm S/G	F71	PF0518	T10 Tape
10mm-12mm	F72	Wet Glazing	
18mm S/G	F72	PF0688-4mm	T10 Tape
20mm S/G	F72	PF0688-5mm	T10 Tape
22mm S/G	F72	PF0518	T10 Tape







Applicable Systems


Comet Awning Window Apollo Awning Window Titan Awning Window Apollo Casement Window Titan Casement Window

Applicable Profiles

F70 Vista Sash F73 Vista Hook Sash




Glazing (A)	Wedge (B)	Captive Wedge (C)
4mm S/G	PF0774-1	PX0005
5mm S/G	PF0774-2	PX0005
6mm S/G	PF0774-3	PX0005
8mm S/G	PF0774-5	PX0026
10mm S/G	PF0829	PX0026




DJ125 Frame DF606 SG Pocket Reducer

Pocket width: 14.7mm Glazing block: 12mm

Pocket Reducers:







Applicable Profiles


DJ125 Frame DJ126 Sill



Glazing (A)	Wedge (B)	Captive Wedge (C)
4mm S/G	PF0774-1	PX0005
5mm S/G	PF0774-2	PX0005
6mm S/G	PF0774-3	PX0005
8mm S/G	PF0774-5	PX0026
10mm S/G	PF0829	PX0026








Applicable Profiles

DJ125 Frame DJ129 NarrowFrame DJ126 Beaded Sill




Glazing (A)	Wedge (B)	Captive Wedge (C)
4mm - 5mm	Wet Glazing	
6mm S/G	PF0774-3 PX0041	
8mm S/G	Wet Glazing	



CA300 Frame

Pocket width: 13.8mm Glazing block: 12mm

Beads:



Applicable Systems


7635-SG Centre Glazed

Applicable Profiles

CA300 Frame CA301 Sill CA302 Sill Bead CA303 Adapter CA308 Corner Post




Glazing (A)	Wedge (B)	Captive Wedge (C)
4mm S/G	PF0774-1	PX0005
5mm S/G	PF0774-2	PX0005
6mm S/G	PF0774-3	PX0005
8mm S/G	PF0774-5	PX0026
10mm S/G	PF0829	PX0026



CA460 Frame

Pocket width: 14.7mm Glazing block: 12mm

Beads:



Applicable Systems

10044-SG Centre Glazed 15044-SG Centre Glazed

10044-SG


CA460 Frame CA461 Sill CA462 Sill Bead CA463 Adapter

15044-SG

CA600 Frame CA601 Sill CA602 Sill Bead CA608 Self Mating Mullion



Glazing (A)	Wedge (B)
4mm S/G	Wet Glazing
5mm S/G	PF0774-4
6mm S/G	PF0774-5
8mm S/G	Wet Glazing



Pocket width: 14.2mm Glazing block: 12mm

Applicable Systems


10044-SG Centre Glazed


Applicable Profiles

CA417 Frame CA414 Corner Post CA464 Split Mullion CA416 H/D Mating Mullion CA424 Narrow Frame



Glazing (A)	Wedge (B)	Captive Wedge (C)
18mm D/G	PF0688-5	PX0096
20mm D/G	PF0774-4	PX0096
22mm D/G	Wet Glazing	
24mm D/G	PF0774-2	PX0005
26mm D/G	PF0774-3	PX0026
28mm D/G	PF0774-5	PX0026





Applicable Systems


10044-SG Centre Glazed

Applicable Profiles

CA500 Frame CA502 Sill CA503 Sill Bead CA504 H/D Adapter




Glazing (A)	Wedge (B)	Captive Wedge (C)
20mm D/G	Wet G	Blazing
22mm D/G	PF0774-1	PX0096
24mm D/G	PF0774-3	PX0096
26mm D/G	PF0774-5	PX0096
28mm D/G	PF0774-2	PX0005
30mm D/G	PF0774-3	PX0026
32mm D/G	PF0774-5	PX0026



CA400 Frame

Pocket width: 38.0mm Glazing block: 17mm

Beads:




|--|


10055-DG Centre Glazed 15055-DG Centre Glazed

Applicable Profiles		
10055-DG/SG 15055-DG		
DF400 Frame	DF600 Frame	
DF401 Sill	DF601 Sill	
DF402 Sill Bead	DF602 Sill Bead	
DF403 Adapter	DF603 Adapter	
DF404 Split Mullion	DF604 Self Mating Mullion	
DF407 Corner Post		



Glazing (A)	Wedge (B)	Captive Wedge (C)
4mm S/G	PF0774-1	PX0005
5mm S/G	PF0774-2	PX0005
6mm S/G	PF0774-3	PX0005
8mm S/G	PF0774-5	PX0026
10mm S/G	PF0829	PX0026





Applicable Systems


10055-SG Front Glazed 15055-SG Front Glazed

Applicable Profiles		
10055-SG	15055-SG	
FG112 Mullion FG117 Female Split Mullion FG118 Male Split Mullion FG108 Transom Sill FG114 Transom FG106 Sill FDG509 Bead	FG601 Transom Sill FG602 Box Transom FG603 Frame FG605 Female Split Mullion FG606 Male Split Mullion FG607 Sill FDG507 Bead FDG509 Bead	

Externally glazed:11mm Internally glazed:14mm




Glazing (A)	Wedge (B)	Captive Wedge (C)
20mm D/G	Wet G	Blazing
22mm D/G	PF0774-1	PX0096
24mm D/G	PF0774-3	PX0096
26mm D/G	PF0774-5	PX0096
28mm D/G	PF0774-2	PX0005
30mm D/G	PF0774-3	PX0026
32mm D/G	PF0774-5	PX0026



FDG511 Mullion

Pocket width: 38.0mm Glazing block: 16mm

Beads:




Applicable Systems
10055-DG Front Glazed
15055-DG Front Glazed

Applicable Profiles			
10055-DG	15055-DG		
FG112 Mullion FG117 Female Split Mullion FG118 Male Split Mullion FG108 Transom Sill FG114 Transom FG106 Sill FDG509 Bead	FG600 Frame FG601 Sill/Transom FG602 Male Split Mullion FG603 Female Split Mullion FG604 Sill / Transom FG606 Sill / Transom FDG507 Bead FDG509 Bead		




Glazing (A)	Frame (B)	Snap Cover (C)	Backing (D)	Caulking (E)
4mm - 6mm S/G	Single Glazed	CA107 / CA108	6mm Structural Glazing Tape	Caulking
8mm - 12mm S/G	Single Glazed	CA120 / CA121	6mm Structural Glazing Tape	Caulking
20mm - 26mm D/G	Single Glazed with Adapter	CA107 / CA810	6mm Structural Glazing Tape	Caulking
20mm - 26mm D/G	Double Glazed	CA107 / CA810	6mm Structural Glazing Tape	Caulking




Pocket width: 4-6 Glass: 15.8mm 8-12 Glass: 21.8mm 20-26 Glass: 34.8mm Glazing block: 10mm


Snap Covers:







CA111 S/G Frame with CA809 Adapter CA810 Snap Cover




Pocket width: 4-6 Glass: 15.8mm 8-12 Glass: 21.8mm 20-26 Glass: 34.8mm Glazing block: 10mm

Applicable Systems

10350 Flush Glazed



Glazing (A)	Bead (B)	Wedge (C)	Backing (D)
4mm - 10mm	CA412	Wet Glazing	
18mm - 24mm	CA703	Wet Glazing	
26mm D/G	CA703	PF0513	T10 Tape
28mm D/G	CA703	PF0518-4mm	T10 Tape
30mm D/G	CA703	PF0519-5mm	T10 Tape



FG112 Mullion

Pocket width:


CA412 Bead: 16.7mm CA703 Bead: 34.2mm


Glazing block:

Single glazed: 13mm

Double glazed: 5mm + 6mm

Beads:





Applicable Systems


Centre Glazed Inline Sash Front Glazed Inline Sash


Applicable Profiles


FDG520 Inline Sash FDG522 Inline Hook Sash



Glazing (A)	Profiles(B)	Wedge (C)	Captive Wedge (D)
4mm S/G	Single Glazed	Wet Glazing	
5mm S/G	Single Glazed	PF0774-4	
6mm S/G	Single Glazed	PF0774-5	
8mm S/G	Single Glazed	Wet Glazing	
18mm - 22mm	Double Glazed	Wet Glazing	
24mm D/G	Double Glazed	PX0084	PX0646
26mm D/G	Double Glazed	Wet Glazing	









Applicable Systems


Thermally Broken Centre Glazed



Glazing (A)	Bead (B)	Wedge (C)	Backing (D)
4mm S/G	ULT-B14	Wet Glazing	
6mm S/G	ULT-B14	PF0513	T10 Tape
8mm S/G	ULT-B14	PF0518	T10 Tape
18mm - 22mm	ULT-B30	Wet Glazing	
24mm D/G	ULT-B30	PF0518	T10 Tape







Applicable Systems


Ultramax Plus Awning/Casement Ultramax Casement


Applicable Profiles


ULT-S402 Ultramax Plus Sash ULT-S62 Ultramax Sash



Glazing (A)	Channel (B)	Profiles (C)
4mm S/G	PF0742	Single Glazed
5mm S/G	PF0843	Single Glazed
6mm S/G	PF0636	Single Glazed
12mm S/G	Wet Glazing	Double Glazed
18mm - 22mm	Wet Glazing	Double Glazed
24mm D/G	PF0551	Double Glazed









Applicable Systems

Titan Apartment Door Ultramax Apartment Door BIF Apartment Door



Glazing (A)	Wedge (B)	Captive Wedge (C)
24mm D/G	PF0774-3	PX0096
26mm D/G	PF0774-5	PX0096
28mm D/G	PF0774-2	PX0005
30mm D/G	PF0774-3	PX0026
32mm D/G	PF0774-5	PX0026





TB003 Frame


Pocket width: 38.0mm Glazing block: 17mm


Ann	licah	ום פו	/stems

10755CG 16055CG



Glazing (A)	Glazing wedge (B)	Captive wedge (C)
36mm D/G	PF0774-3	PX0096
38mm D/G	PF0774-5	PX0096
40mm D/G	PF0774-2	PX0005
42mm D/G	PF0774-3	PX0026
44mm D/G	PF0774-5	PX0026






Pocket width: 50.0mm Glazing block: 15mm




Glazing (A)	Wedge (B)	Captive Wedge (C)
24mm D/G	PF0774-2	PX0646
26mm D/G	PF0774-4	PX0646



TB011

Pocket width: 36.0mm Glazing block: 8mm

Beads:




Applicable Systems

Thermally Broken Sliding Door Thermal Hinge Door




Glazing (A)	Bead (B)	Wedge (C)	Backing (D)
24mm D/G	TB037	PX0085	PX0642
26mm D/G	TB038	PX0085	PX0642
28mm D/G	TB039	PX0087	PX0642
30mm D/G	TB039	PX0085	PX0642



Pocket width: 30.0mm Glazing block: 5mm

Beads:




Applicable Systems

Thermally Broken Centre Glazed



Glazing (A)	Wedge (B)	Captive Wedge (C)
20mm D/G	PF0688-4mm	T10 Tape
24mm D/G	PF0519-5mm	T10 Tape
26mm D/G	PF0519-6mm	T10 Tape




Applicable Profiles

TB100 Frame TB111 Frame Coupler TB103 Box Transom TB112 Hook Head Frame



Glazing (A)	Wedge (B)	Captive Wedge (C)
20mm D/G	PF0688-4mm	T10 Tape
24mm D/G	PF0519-5mm	T10 Tape
26mm D/G	PF0519-6mm	T10 Tape




Applicable Profiles

TB100 Frame TB111 Frame Coupler TB103 Box Transom TB112 Hook Head Frame



Glazing (A)	Wedge (B)	Baking (C)
20mm D/G	PF0688-4mm	T10 Tape
24mm D/G	PF0519-5mm	T10 Tape
26mm D/G	PF0519-6mm	T10 Tape



TB101 Sash

Pocket width: 28.5mm Glazing block: 5mm

Applicable Systems

TB102 Hook Head Sash