
2025



Residential Window and Door Systems Product Catalogue





Index

Sliding Windows

- 5 Comet Sliding Window
- 8 Zeus Sliding Window
- 11 Ultramax Sliding Window

Double Hung Windows

- 15 Zeus Double Hung Window
- 18 Ultramax Double Jung Window
- 21 Apollo Accessory Window Frame

Awning/Casement Windows

- 23 Comet Awning Window
- 27 Apollo Awning/Casement Window
- 31 Titan Awning/Casement Widow
- 35 Ultramax Plus Awning/Casement Window

Door Systems

- 38 Windsor Bi-Fold Door
- 43 Comet Sliding Door
- 47 Comet Stacker Door
- 51 Artemis Series (12532CG)
- 56 Titan Built In Fly-track (BIF) Apartment Door



^{**}Please note this catalogue is updated every 6 months and may exclude new profiles or hardware added between this time.

^{**}Front cover photo credits to AAA Somerton Windows Last updated: 4/12/2025

Powder Coating

Concept Aluminium Systems is committed to providing customers with exceptional powder coating services.

As an accredited applicator with both Dulux and Interpon, we offer an extensive range or coatings and colours that can be tailored to each customers needs.

Our specialised seven stages pre-treatment facility complies with the requirements of AS3715. This ensures that our products meet stringent performance and durability standards.

With two automatic horizontal paint lines and the latest state of the art equipment, you can rest assured that your job will be completed on time and to the highest quality.





Tooling for Success

Concept Aluminium Systems recognises the importance of tooling as an integral part of the manufacturing process. All tooling required for the manufacture of Concept Aluminium Systems' products is designed and built to meet the specific requirements of each fabricator.

We perform a detailed needs analysis to determine the necessary machining functions required to manufacture the product ranges you wish to supply.

Our staff will visit your promises to ensure the tooling we supply suits your factory's layout and existing set up. We take into consideration things such as three phrase power availability, pneumatic air capacity and hydraulic drives.

In collaboration with Alumach Aluminium Fabrication Equipment and FOM Industries, we have developed the following three standard tooling packages:

In collaboration with Alumach Aluminium Fabrication Equipment and FOM Industries, we have developed the following three standard tooling packages.

These packages include either a CNC Machining Center or a copy router and end milling machine, a double miter saw, and a set of workbenches.


These packages are ideal for new fabricators getting started or for existing fabricators looking to upgrade their equipment.


CAS tooling packages:

- Silver
- Gold
- Platinum

Comet Sliding Window

Entry-Level Sliding Window





WERS

U-Value	SHGC	TVW
3.2 - 6.3	0.21 - 0.73	0.25 - 0.75

PERFORMANCE -

Exposure Condition: N3

Serviceability	Ultimate Pressure	Water Penetration
(+Pa)	(+Pa)	(Pa)
ир то	ир то	ир то
500	2000	150

FEATURES -

- Frame: 38mm x 48mm
- Double Glazing: 18mm (with adapters)
- Single Glazing: 4mm 6.38mm
- 18kg stainless steel bearing rollers
- Lockable window latch
- Lockable window restrictor
- Low profile frame and sash
- 24kg sash

Comet Sliding Window Profiles





Head CSW1 Length: 6000



Sill CSW2 Length: 6000



Jamb CSW3 Length: 6200



Transom CSW5 Length: 6000




Rail CSW8 Length: 6000



Lock Stile CSW6 Length: 6000



Interlock CSW7 Length: 6000



Mullion CSW4 Length: 6000



Heavy Duty Mullion CSW20 Length: 6000



Fixed Panel Glazing Bead CSW12 5000mm



Double Glazing Adapter CSW17 Length: 6000



Track Cover / Limiter CSW18 Length: 4000



Reveal Closer F60 Length: 6000



Extended Frame Closer F61 Length: 6000





Back to Back Coupler CSW9 Length: 6000



Corner Coupler

BC50

Length: 6000



Bay Window Coupler CSW10 Length: 6500

Hardware/Accessories





Lock

SWL50 Box of 100



Roller SWR50 Bag of 200



Guide SWG50 Bag of 200



Limiter Lock DS255U



Anti-Lift Block DS470 Pair of 250 pairs



Sash Corner Flute CS51 Bag of 1000



4.8mm x 5.5mm Wool PileWP48550
Roll of 450m



Fly screen Leaf Spring 1633 Bag of 100



End Cap To suit CSW20 ECD20



Sill Flap PF0628 Roll of 150m



Sill Baffle PX0040 Roll of 300m



Expansion Seal PX0049 Pack of 60m



Head Gasket GF52 Roll of 250 Pairs



Sill Gasket GF54 Roll of 250 Pairs



Transom GasketGF53
Roll of 250 Pairs



4mm Channel Sliding Window Sash PF0634 Roll of 175m



5mm Channel Sliding Window Sash PF0659 Roll of 200m



6mm Channel Sliding Window Sash PF0553-6 Roll of 200m



18mm D/G Channel PF0830 Roll of 150m



10mm Glazing TapeT10
Roll of 46m



4mm Sliding/Awning Fixlite Wedge PF0688-4MM Roll of 100m




5mm Sliding/Awning Fixlite Wedge PF0688-5MM Roll of 125m



6mm Sliding/Awning Fixlite Wedge PF0687-6MM Roll of 150m

Zeus Sliding Window

High-End Sliding Window



The Zeus Sliding Window is our deluxe sliding window, designed to be compact yet robust, creating the feeling of a commercial grade window. Designed with a 90mm frame this systems is extremely flexible and can be used in a range of residential projects, and low lying commercial projects. The Zeus Sliding Window is complimented by high quality hardware including a flush mounted lock which enhances this system by creating a high-quality finish and effortless operation.

creating a high-quality finish and effortless operation.

WERS

U-Value	SHGC	TVW
3.3 - 6.3	0.20 - 0.59	0.22 - 0.61

PERFORMANCE -

Exposure Condition: N3

Serviceability (+Pa)	Ultimate Pressure (+Pa)	Water Penetration (Pa)
UP TO	UP TO	UP TO
1000	3300	300

- Frame: 90mm x 60mm
- Double Glazing: 18mm
- Single Glazing: 4mm 6.38mm

FEATURES

- Dual 100kg stainless steel ball-bearing rollers
- Advance Sump sill drainage
- Suitable for corner window configurations

Zeus Sliding Window Profiles





Head DGS86 Length: 6000




Sill / Transom DGS85 Length: 6000



Jamb DGS90 Length: 6000



Low-Lite Mullion DGS71 Length: 6000



Track Infill DGS87

Length: 6000



Fly-screen Channel **Adapter** DGS88 Length: 6000



Plant-On Fly-screen Adapter DGS89 Length: 6000



S/G Lock Stile


DGS92 Length: 6000



S/G Interlock CSD6 Length: 4900/6500




S/G Heavy Duty Interlock STK4 4900 / 6500



S/G Male Stile CSD5 Length: 6000 4900/6500



S/G Female Stile STK7 Length: 6500



S/G Rail CSD4 Length: 6500




D/G Lock Stile DGS98 Length: 6500



D/G Interlock DGS97 Length: 4900/6500




D/G Heavy Duty Interlock DGS80 Length: 4900/6500



D/G Male Stile DGS96 Length: 4900/6500




D/G Female Stile DGS82 Length: 6500



D/G Rail DGS81 Length: 6000



Fixed Panel Adapter Track DGS70 Length: 6000



D/G Sliding Sill **Adapter** DGS72 Length: 6000



Fixed Panel Bead S/G 4mm - 6mm F56

Length: 6000



Fixed Panel Bead S/G 8mm - 12mm F65 Length: 6000



D/G 18mm -22mm F55 Length: 6000





Reveal Closer F60 Length: 6000

Zeus Sliding Window Profiles





Extended Frame Closer F61

Length: 6000




Slotted Sub sill SH102

Length: 6500



90mm Sub sill Frame SH105

Length: 6000



Subhead

SH103 Length: 6500



90mm 2 Piece Sub **Jamb**

SH100 Length: 6500



Sub Jamb Cover CA605 Length: 6500



135° Bay Coupler

F135

Length: 6000 To suit 90mm

AluRES Frames



40kg Narrow Roller DR3


Box of 200 / or separately





Narrow Dummy Roller

separately





Limiter Lock DS255U



100kg Dual Wheel Roller

8358 Box of 100 / or separately



Bump Stop

BS33 Bag of 100



Door Stop

Black 1690-B Box of 100



Door Stop Satin Chrome

1690-C Box of 100



Anti-Lift Block

DS470 Pair of 2



Fixed Panel Fixing Block

LB1

Bag of 500



End Cap to Suit SH105 Sub sill

Right EC105R



End Cap to Suit SH105 Sub sill Left

EC105L

Bag of 200

Ultramax Sliding Window

Commercial Grade Sliding Window



The Ultramax Sliding Window is a premium heavy-duty system designed to integrate seamlessly with the 10055-DG/SG Centre Glazed Framing System, enabling fixed and sliding window combinations. Its sliding operation maximises usable space, making it ideal for high-traffic environments such as schools and nursing homes. When specified with the optional narrow frame, it also offers a sleek aesthetic suited to modern

residential applications.

WERS

U-Value	SHGC	TVW
3.7 - 6.5	0.19 - 0.57	0.20 - 0.57

PERFORMANCE —

Exposure Condition: N4

Serviceability	Ultimate Pressure	Water Penetration
(+Pa)	(+Pa)	(Pa)
ир то	ир то	ир то
1000	2000	300


Acoustic Ratings: RW 24-33

FEATURES -

- Standard Frame: 84mm x 101mm
- Narrow Frame: 60mm x 101mm (requires sub sill)
- Double Glazing: 18mm (with adapter)
- Single Glazing: 4mm 6.5mm
- Dual 100kg s/s bearing rollers
- Slimline mortice lock
- Uses the 10055-DG Center Glazed
- Combinations of sliding and fixed
- Integrated sump/sill transom

Ultramax Sliding Window Profiles





Sill / Transom DF416 Length: 6500




Narrow Sill DF415 Length: 6500



55mm Jamb DF400 Length: 6500




30mm Jamb with Reveal Fin DF414 Length: 6500



Jamb Adapter DF410 Length: 6500




Frame Flat Filler DF605 Length: 6500




Sub sill with Reveal Fin
SS21
Length: 6500




Reveal Adapter CA490 Length: 6500



Ezy Reveal Adapter CA450 Length: 6500



er CA493 Length: 6500




Track Infill DGS87 Length: 6000



Fly-screen Channel Adapter DGS88 Length: 6000



Plant-On Fly-screen Adapter DGS89 Length: 6000



S/G Lock Stile DGS92 Length: 6000




S/G Interlock CSD6 Length: 4900/6500



S/G Heavy Duty Interlock STK4

Length: 4900/6500



S/G Male Stile


Length: 4900/6500



S/G Female Stile

STK7

Length: 6500



S/G Rail CSD4

Length: 6500



D/G Lock Stile

DGS98 Length: 6500




D/G Interlock

DGS97 Length: 4900/6500



D/G Heavy Duty Interlock DGS97

4900 / 6500mm



D/G Male Stile

DGS96 Length: 4900/6500



D/G Female Stile

DGS82 Length: 6500



D/G Rail

DGS81

Length: 6000

Hardware / Accessories





40kg Narrow RollerDR3
Box of 200 / or separately



Narrow Dummy Roller DR4 Box of 200 / or separately



100kg Dual Wheel Roller 8358 Box of 100 / or separately



Bump Stop BS33 Bag of 100



Door Stop Black 1690-B Box of 100



Door Stop Satin Chrome 1690-C Box of 100



Limiter Lock DS255U



Anti-Lift Block DS470 Pair of 2



Fixed Panel Fixing Block LB1 Bag of 500



Interlock Block LB4 Bag of 250



Interlock End Cap Black / White / Grey EC60 Box of 400



Fly-screen Clip FC1 Box of 500



Weep Hole Cover WHC1239 Bag of 100



10mm Hole Plug HP10 Bag of 200



27mm End Cap Suit STK7 / DGS82 ECD27MM Bag of 200



Sub sill End Cap - Left Suit SS21 EC21L Bag of 100



Sub sill End Cap -Right Suit SS21 EC21R Bag of 100



4.8mm x 5.5mm Wool Pile WP48550 Roll of 450m



4.8mm x 7.5mm Acoustic SealQL48750
Roll of 600m



Sill Flap PF0628 Roll of 150m



Co-Ex Sill Baffle PX0040 Roll of 300m



Head / Sill Gasket Suit DF416 GF109 Roll of 100 Pairs



Narrow Sill Gasket Suit DF415 GF108 Roll of 100 Pairs



4mm Sliding Door Channel PF0742 Roll of 100m



5mm Sliding Door Channel PF0843 Roll of 100m

Hardware/Accessories






6mm Sliding Door Channel PF636 Roll of 100m



18mm D/G Channel PF0830 Roll of 150m

Zeus Double Hung Window

High-End Double Hung Window



The Zeus Double Hung Window offers a timeless design that does not project outwards, making it perfect for spaces with limited room. It provides excellent ventilation and is designed for easy cleaning and minimal maintenance. Its 90mm frame pairs effortlessly with other 90mm windows, allowing you to create a variety of configurations to suit any design. Paired with luxe stainless steel hardware, the Zeus Double Hung Window combines style and functionality, standing out as a feature in any home.

—— PERFORMANCE ————— FEATURES ————

WERS

U-Value	SHGC	TVW
3.1 - 6.5	0.22 - 0.69	0.31 - 0.7


Exposure Condition: N3

Serviceability (+Pa)	Ultimate Pressure (+Pa)	Water Penetration (Pa)
UP TO	UP TO	UP TO
600	1400	200


- Frame: 60mm x 90mm
- Double Glazing: 18mm
- Single Glazing: 4mm-6mm
- Optional sub framing
- Adjustable rollers for simple assembly
- No punch tooling required
- Can be coupled with existing 90mm frames

Zeus Double Hung Window Profiles





Sill DHW90 Length: 6000



Jamb DHW91 Length: 6000



Head DGS86 Length: 6000



Centre Jamb Guide DHW92 Length: 6000



Inner/Outer Jamb Guide DHW93 Length: 6000



Track Infill DGS87 Length: 6000



Rail **Single Glazed DHW100** Length: 6000



Stile Single Glazed DHW101 Length: 6000



Rail **Double Glazed DHW102** Length: 6000




Stile **Double Glazed** DHW103 Length: 6000



Interlock Insert DHW105 Length: 6000



Handle Insert DHW104 Length: 6000



Slotted Sub sill SH102 Length: 6000



90mm Sub sill Frame SH105 Length: 6000




Reveal Closer F60 Length: 6000




Extended Frame Closer F61

Length: 6000



Subhead SH103 Length: 6000



Back to Back Coupler **DHW106** Length: 6000



Adapter Length: 6000



90° Corner Coupler BC90 Length: 6000



135° Bay Coupler

F135 Length: 6000 To suit 90mm **AluRES Frames**



20mm Colonial

Bar F75

Length: 3600

Hardware/Accessories





Double Hung Lock Black DHL110-BLK



Double Hung Lock ChromeDHL110-SC



36mm Adjustable Pulley CR110



3mm Sash Cord

DHC110 Roll of 500m



Cord Retaining Clip DHR110 Bag of 200



4.8mm x 6.5mm WP69500 WP48650 Roll of 450m



Bump Strip BS473 Roll of 25m



Interlock End Cap Left EC30L Bag of 100



Interlock End Cap Right EC30R Bag of 100



End Cap to Suit SH105 Sub sill Left EC105L Bag of 200



End Cap to Suit SH105 Sub sill Right EC105R



Q-Lon Sill Seal QEZ48 Roll of 305m



Sill Flap PF0628 Roll of 150m



Expansion Seal PX0049 Pack of 60m



Sill Gasket GF111 Roll of 50 Pairs



Head Gasket GF94 Roll of 250 Pairs



4mm Sliding Door Channel PF0742 Roll of 100m



5mm Sliding Door Channel PF0843 Roll of 100m



6mm Sliding Door Channel PF636 Roll of 100m




18mm D/G Channel PF0830 Roll of 150m

Ultramax Double Hung Window

Commercial Grade Double Hung Window





WERS

U-Value	SHGC	TVW
3.3 - 4.3	0.21 - 0.57	0.24 - 0.59

PERFORMANCE

Exposure Condition: N3

Serviceability (+Pa)	Ultimate Pressure (+Pa)	Water Penetration (Pa)
UP TO	UP TO	UP TO
8100	3000	400

- FEATURES

- Frame: Various available
- Double Glazing: 18mm
- Single Glazing: 4mm 6.38mm
- Innovative adjustable roller
- Simple cord mounting mechanism
- Couples with any 100mm or 150mm
 AluCOMM Commercial Centre Glazed
 Frame
- Large sash sizes
- Optional sub framing available


Center Glazed Ultramax Double



Hung Window




S/G head/Sill Adapter DHW111 Length: 6500 To suit CA460




S/G Jamb Adapter DHW110 Length: 6500 To suit CA460



10055-DG Pocket Reducer DF606 Length: 6500 To suit DF400



10044-DG Head/ Sill Adapter DHW116 Length: 6500 To suit CA500



10044-DG Jamb Adapter DHW115 Length: 6500 To suit CA500



Center Jamb Guide DHW92 Length: 6000



Outer Jamb Guide DHW93 Length: 6000



S/G Rail DHW100 Length: 6500



S/G Stile DHW101 Length: 6000



D/G Rail DHW102 Length: 6000



S/G Stile DHW103 Length: 6000



Interlock Insert DHW105 Length: 6000



Handle Insert DHW104 Length: 6000



Track Flat Filler DGS87 Length: 6000

Hardware / Accessories



6.38mm Channel Rubber PF0636



5mm Channel Rubber PF0843



4mm Channel Rubber PF0742



18mm Channel Rubber PF0830



Bump Strip BS473

Hardware / Accessories





Double Hung Lock Kit - Chrome DHL110-SC



Double Hung Lock Kit - Black DHL110-BLK



Adjustable Pulley CR110



3mm Sash Cord DHC110



Cord Retaining Clip DHR110



Q-Lon Seal QEZ48



6.5mm Wool Pile WP48650



Interlock End Cap Left EC30L




Interlock End Cap Right EC30R

Apollo Accessory Window Frame

Louvers, Sashless Windows, and more






WERS U-Value SHGC **TVW** N/A N/A N/A **Configuration dependent** Serviceability **Ultimate Pressure Water Penetration** (+Pa) (+Pa) (Pa) UP TO UP TO UP TO N/A N/A N/A

PERFORMANCE -

- FEATURES
- Frame: 26mm x 90mm
- Double Glazing (center aluminium bar): configuration dependent
- Single Glazing: configuration dependent
- Optional sub framing available
- Compatible with wide range of sashless units, aluminium louver blades, and glass louver blades

Apollo Sashless Window Profiles





Frame F100 Length: 6000 Flat Filler F101 Length: 6000

Comet Awning / Fixed Window

Entry-Level Awning Window



The Comet Awning / Fixed Window is a simple, cost-effective system that does not comprise on energy performance. A low-profile frame Is used which gives a slimline appearance and can create narrow awning windows which are ideal in bathrooms, kitchens, and laundries. Entry level homes, units, and townhouses are ideal application uses, as well as being a top choice for renovations or partial renovations where a few windows need replacing.

———— PERFORMANCE ———— FEATURES ————

WERS

U-Value	SHGC	TVW
2.2 - 6.4	0.16 - 0.78	0.20 - 0.64

Exposure Condition: N4

Serviceability (+Pa)	Ultimate Pressure (+Pa)	Water Penetration (Pa)
UP TO	UP TO	UP TO
800	2000	300

- Frame: 50mm x 20mm
- Double Glazing: 18mm 24mm
- Single Glazing: 4mm 6.38mm
- Hook head awning design
- Compatible with awning stays
- Dual seal sash
- Standard sash options available

Comet Awning Window Profiles





Frame F50 Length: 6000



Hook Head F58 Length: 6000



Transom F51 Length: 6000



Adapter F52 Length: 6000




Chain Winder Adapter F57

Length: 5400




Sash **Single Glazed**



Hook Sash Single Glazed



Sash **Double Glazed**



Hook Sash Double Glazed



Fixed Panel Bead S/G 4mm - 6mm F56

Length: 6000

Length: 6000











Fixed Panel Bead S/G 8mm - 12mm

Length: 6000



Fixed Panel Bead D/G 18mm -22mm F55

Length: 6000



Fixed Panel Bead D/G 24mm

F64 Length: 6000



Reveal Closer

F60

Length: 6000



Extended Frame Closer

F61

Length: 6000



20mm Colonial Bar F75

Length: 3600



Back to Back Coupler CSW9

Length: 6000



Corner Coupler

BC50

Length: 6000



Bay Window Coupler

CSW10

Length: 6500

Hardware/Accessories





Chain Winder Black GW380217-CD1



Chain Winder DS1 Black & white



Twin Chain Winder CW2 Black



Edge Cam Handle Left Hand EDGE3111B



Edge Cam Handle Right Hand EDGE3110B



Sash Corner Stake CS50 Box of 1000



Sash Corner Flute CS51 Bag of 1000



Awning Wedge AW1 Bag of 500



Fly-screen Clip FC1 Box of 500



Weep Hole Cover WHC1239 Bag of 100



Chain Winder Adapter End Cap EC50 Bag of 500



10kg Awning Stay Non Friction200-4B-NF
Pair of 2



20kg Awning Stay Non Friction 350-NB-NF Pair of 2



30kg Awning Stay Non Friction 500-NB-NF Pair of 2



Awning Stay 100mm Restrictor P1097



6mm Bulb Seal PX0644 Roll of 250m



V-Seal PX0642 Roll of 300m



Sill Flap PF0628 Roll of 150m



Expansion Seal PX0049 Pack of 60m



Frame Gasket GF50 Roll of 250 Pairs



Transom Gasket GF51 Roll of 250 Pairs



Sash Cutting Block Kit SCB



Chain Winder Foam Block NP383



Fixed Wedge 4 / 8 / 18mm PF0688-4MM Roll of 100m



Fixed Wedge 5 / 24mm PF0688-5MM Roll of 125m

Hardware/Accessories





Fixed Wedge 6 / 10 / 20 / 24.76mm
PF0687-6MM
Roll of 150m



Fixed Wedge 12 / 22mm PF0518-4MM Roll of 200m



Fixed Foam Glazing Tape T10 Roll of 46m



Sash Wedge 4 / 5mm PF0519-5MM Roll of 200m






Sash Wedge 24mm PF0519-6.38MM Roll of 250m




Sash T-Back PX0091 Roll of 300m

Apollo Awning / Casement Window

Mid-Range Awning Window





	PERFORMANCE	
WERS		
U-Value	SHGC	TVW
2.4 - 6.6	0.16 - 0.77	0.20 - 0.62
Exposure Co	ondition: N4	
Serviceability (+Pa)	Ultimate Pressure (+Pa)	Water Penetration (Pa)
ир то 1200	ир то 2000	ир то 1000
Acoustic Ra	tings:	
Fixed 25	Awning	27 - 34

RW

FEATURES

- Frame: 100mm x 55mm
- Double Glazing: 18mm 24mm
- Single Glazing: 4mm 6.38mm
- Dual 100kg s/s bearing rollers
- Slimline mortice lock
- Optional 70mm vista sash
- Uses a hook head awning design
- Compatible with awning stays
- Optional sub sill


Apollo Awning/Casement Window Profiles





Frame F90

Length: 6000



Hook Head F99

Length: 6000



Transom

F94

Length: 6000



Adapter

F93

Length: 6000



Chain Winder Adapter

F92

Length: 6500



Chain Winder Flat Filler

CA305 Length: 6500



Sash Single Glazed

F53

Length: 6000



Hook Sash Single Glazed

F59


Length: 6000



Sash Double Glazed

F62


Length: 6000



Hook Sash
Double Glazed

F63


Length: 6000



Vista Sash

F70

Length: 6200



Vista Hook Sash

F73

Length: 6200



Fixed Panel Bead S/G 4mm - 6mm

F56

Length: 6000



Fixed Panel Bead S/G 8mm - 12mm

F65

Length: 6000



Fixed Panel Bead D/G 18mm -

22mm

F55

Length: 6000



Fixed Panel Bead D/G 24mm

F64

Length: 6000



Vista Sash Bead Single Glazed

F71

Length: 6200



Vista Sash Bead Double Glazed

F72


Length: 6200



Slotted Sub sill

SH102

Length: 6500



90mm Sub sill

Frame SH105

Length: 6000



Reveal Closer

F60


Length: 6000



Extended Frame Closer

F61

Length: 6000



Back to Back Coupler

Length: 6000

Coupler DHW106



135° Bay Coupler

F135

Length: 6000

To suit 90mm
AluRES Frames



90° Corner Coupler

BC90

Length: 6000

Apollo Awning/Casement Window Profiles



20mm Colonial Bar F75

Length: 3600

Hardware/Accessories



Chain Winder Black GW380217-CD1



Chain Winder DS1 Black & white



Twin Chain Winder CW2 Black



Edge Cam Handle Left Hand EDGE3111B



Edge Cam Handle Right Hand EDGE3110B



Sash Corner Stake CS50 Box of 1000



Vista Sash Corner Stake CS450 Box of 100



Sash Corner Flute CS51 Bag of 1000



Awning Wedge AW1 Bag of 500



Fly-screen Clip FC1 Box of 500



Weep Hole Cover WHC1239 Bag of 100



10kg Awning Stay Non FrictionP1002NF
Pair of 2



20kg Awning Stay Non Friction P1003NF Pair of 2



30kg Awning Stay Non FrictionP1004NF
Pair of 2



Awning/Casement Stay Restrictor 430-4BC-NF Pair of 2

Hardware/Accessories





Awning Stay 100mm Restrictor P1097



Bulb Seal PX0644 Roll of 250m



V-Seal PX0642 Roll of 300m



4.8mm x 7.5mm Acoustic SealQL48750
Roll of 600m



Sill Flap PF0628 Roll of 150m



Expansion Seal PX0049 Pack of 60m



Frame Gasket GF90 Roll of 250 Pairs



Transom Gasket GF91 Roll of 250 Pairs



End Cap to Suit SH105 Sub sill Left EC105L Bag of 200



End Cap to Suit SH105 Sub sill Right EC105R



Sash Cutting Block Kit SCB



Chain Winder Foam Block NP383



Fixed Wedge 6 / 10 / 20 / 24.76mm
PF0687-6MM
Roll of 150m



Fixed Wedge 4 / 8 / 18mm PF0688-4MM Roll of 100m



Fixed Wedge 5 / 24mm PF0688-5MM Roll of 125m



Sash Wedge 18mm PF0688-4MM Roll of 100m



Sash Wedge 20mm PF0688-5MM Roll of 125m



Fixed Wedge 12 / 22mm PF0518-4MM Roll of 200m



Fixed Foam Glazing Tape T10 Roll of 46m



Sash Wedge 4 / 5mm PF0519-5MM Roll of 200m



Sash Wedge 6mm PF0968-6MM Roll of 350m




Sash Wedge 24mm PF0519-6.38MM Roll of 250m



Sash T-Back Glazing PX0091 Roll of 300m

Titan Awning / Casement Window

High-End Awning Window



The Titan Awning Window is a heavy-duty system that is designed for projects that require large openings and glass surfaces without small restrictions on sizes The Titan Awning Window features a large frame that can handle exceptional wind load and water penetration making it ideal for projects that require strength and top performance. High end residential applications and architectural builds are ideal to feature this

bold awning window.

WERS

U-Value		SHGC	

0.15 - 0.73

PERFORMANCE

TVW

0.17 - 0.56

Exposure Condition: N4

Serviceability (+Pa)
UP TO
1500

2.8 - 6.5

Ultimate Pressure (+Pa)

UP TO 2250 **Water Penetration** (Pa)

> UP TO 1000

Frame: 90mm x 44mm

Double Glazing: 18mm - 24mm

FEATURES

Single Glazing: 4mm - 6.38mm

Dual seal sash

Optional 70mm Vista sash

Compatible with awning stays

Uses a hook head awning design

Optional sub sill

Titan Awning/Casement Profiles





Frame F91 Length: 6000



Hook Head F82 Length: 6000



Transom F95 Length: 6000



Adapter F93 Length: 6000



F75 Length: 3600



Chain Winder Adapter F92 Length: 6500



Chain Winder Flat Filler CA305 Length: 6500



Sash Single Glazed F53 Length: 6000




Hook Sash Single GlazedF59

Length: 6000



Sash Double Glazed F62 Length: 6000




Hook Sash Double Glazed

Length: 6000



Vista Sash

Length: 6200



Vista Hook Sash F73 Length: 6200



Fixed Panel Bead S/G 4mm - 6mm F56

Length: 6000



Fixed Panel Bead S/G 8mm - 12mm

F65


Length: 6000



Fixed Panel Bead D/G 18mm - 22mm

F55

Length: 6000



Fixed Panel Bead D/G 24mm

F64

Length: 6000



Vista Sash Bead Single Glazed

F71

Length: 6200



Vista Sash Bead Double Glazed

F72

Length: 6200



Reveal Closer

F60


Length: 6000



Extended Frame Closer

F61


Length: 6000



Slotted Sub sill

SH102


Length: 6500



Subhead

SH103


Length: 6500



90mm Sub sill Frame

Frame SH105

Length: 6000



Back to Back Coupler

DHW106 Length: 6000

Titan Awning/Casement Profiles





90° Corner Coupler BC90 Length: 6000



135° Bay Coupler F135 Length: 6000 To suit 90mm AluRES Frames



90mm 2 Piece Sub Jamb SH100 Length: 6500



Sub Jamb Cover CA605 Length: 6500

Hardware/Accessories



Chain Winder Black GW380217-CD1



Chain Winder DS1 Black & white



Twin Chain Winder CW2 Black



Edge Cam Handle Left Hand EDGE3111B



Edge Cam Handle Right Hand EDGE3110B



Sash Corner Stake CS50 Box of 1000



Vista Sash Corner Stake CS450 Box of 100



Sash Corner Flute CS51 Bag of 1000



Awning Wedge AW1 Bag of 500



10kg Awning Stay Non Friction 200-4B-NF Pair of 2



20kg Awning Stay Non Friction 350-4B-NF Pair of 2



30kg Awning Stay Non Friction 500-4B-NF Pair of 2



Awning/Casement Stay Restrictor 430-4BC-NF Pair of 2



Awning Stay 100mm Restrictor P1097



4.8mm x 7.5mm Acoustic Seal QL48750 Roll of 600m

Hardware/Accessories





Bulb Seal PX0644 Roll of 250m



V-Seal PX0642 Roll of 300m



Sill Flap PF0628 Roll of 150m



Expansion Seal PX0049 Pack of 60m



Frame Gasket GF92 Roll of 250 Pairs



Transom Gasket GF93 Roll of 250 Pairs



Sash Cutting Block Kit SCB



Chain Winder Foam Block NP383



Fixed Wedge 4 / 8 / 18mm PF0688-4MM Roll of 100m



Fixed Wedge 5 / 24mm PF0688-5MM Roll of 125m



Fixed Wedge 6 / 10 / 20 / 24.76mmPF0687-6MM
Roll of 150m



Fixed Wedge 12 / 22mm PF0518-4MM Roll of 200m



Fixed Foam Glazing Tape T10 Roll of 46m



Sash Wedge 4 / 5mm PF0519-5MM Roll of 200m



Sash Wedge 6mm PF0968-6MM Roll of 350m



Sash Wedge 24mm PF0519-6.38MM Roll of 250m



Sash T-Back Glazing PX0091 Roll of 300m



End Cap to Suit SH105 Sub sill Right EC105R



End Cap to Suit SH105 Sub sill Left EC105L Bag of 200

Ultramax Plus Awning / Casement Window

Commercial Grade Awning/Casement Window





the system.

PERFORMANCE — FEATURES — FEATUR

WERS

U-Value	-Value SHGC T	
4.0 - 6.4	0.14 - 0.46	0.16 - 0.44

Exposure Condition: N3

Serviceability	Ultimate Pressure	Water Penetration
(+Pa)	(+Pa)	(Pa)
ир то	ир то	UР ТО
1000	2500	300

Acoustic Ratings:


RW

29-32

- Standard Frame: 55mm x 101mm
- Narrow Frame: 30mm x 101mm
- Double Glazing: 24mm 30mm
- Single Glazing: 4mm-10.38mm
- Integrates with the 10055-DG
 Centre Glazed System
- Dual seal sash
- Captive wedge available
- Truth stainless steel hardware with multi point locking
- Large range of sub framing options


Ultramax Plus Awning/Casement Profiles





Frame 100mm x 55mm

DF400 Length: 6500



Narrow Frame 100mm x 30mm

DF414 Length: 6500



Head/Sill

ULT-F400 Length: 6500



Narrow Head/Sill

ULT-F31

Length: 6500



Jamb Adapter

ULT-J401 Length: 6500



Sash

ULT-S402 Length: 6500



Sash Bead Single Glazed

ULT-B14 Length: 6500



Sash Bead **Double Glazed**


ULT-B30 Length: 6500



Sub sill with Reveal Fin

SS21


Length: 6500



Reveal Adapter

CA490

Length: 6500



Ezy Reveal Adapter

CA450

Length: 6500



Ezy Reveal Adapter

CA493

Length: 6500

Hardware/Accessories



Sash Corner Stake CS440-L



Sash Corner Flute CS51 Bag of 1000



Sill End Cap ECP1 Bag of 200



Jamb End Cap Left **EC-ULTL** Bag of 200



Jamb End Cap Right **EC-ULTR** Bag of 200





Sub sill End Cap - Left Suit SS21 EC21L Bag of 100



Sub sill End Cap -Right Suit SS21 EC21R Bag of 100



Chain Winder Foam Block NP383



Bulb Seal PX0644 Roll of 250m



Sash Flap PF0924 Roll of 250m



Sill Baffle PX0040 Roll of 300m



Sill Flap PF0628 Roll of 150m



Sash Wedge 6mm PF0513 Roll of 150m



Sash Wedge 8 / 24mm PF0518-4MM Roll of 200m




Fixed Foam Glazing Tape T10 Roll of 46m

Windsor Bi-Fold Door

Commercial Grade Bi-Fold





PERFORMANCE -

WERS

SHGC

TVW

3.1 - 6.0

0.15 - 0.57

0.18 - 0.59

Exposure Condition: N3

Serviceability (+Pa)

UP TO 500

Ultimate Pressure (+Pa)

_{UP} то 1400

Water Penetration (Pa)

ир то 200

FEATURES

- Frame: 44mm x 100mm
- Double Glazing: 24mm
- Single Glazing: 4mm 10.5mm
- 90kg Fully adjustable hardware
- AQ-21 foam door seals
- Edge hardware 3 point locking lever handles
- Sump sill option
- Dual seal door stiles
- One piece head


Windsor Bi-Fold Door Profiles





Head BF1

Length: 4500/6500



Jamb / Frame CA460

Length: 6500



Jamb Adapter

BF3

Length: 6500



Pocket Filler Suit CA460

CA409

Length: 6500



Open Out Sill With Sump

BF2

Length: 6500



Open In Sill Slotted BF10


Length: 6500



Open Out Sill Requires Sub sill

BF13

Length: 6500



Low Step Sill Open In/Open Out

BF14

Length: 6500



Channel Sill Open In/Open Out

BF11

Length: 6500



Mating Stile Single Glazed


Length: 2800/6500



Mating Stile Single Glazed

BF5

Length: 6500



Lock Stile Single Glazed

CD213

Length: 6500



Rail

CD200 Length: 6500

Single Glazed

CD201 Length: 6500

Wide Rail

Single Glazed



Mid rail Single Glazed

CD203 Length: 6500



Mid rail **Single Glazed** CD204

Length: 6500




Rail Bead Single Glazed

CD202 Length: 6500

Meeting Stile Adapter

CA436

Length: 4800



Bi-Fold Stile Deep Pocket

DG923


Length: 6500



Mating Stile Deep Pocket


DG922

Length: 6500



Lock Stile Deep Pocket DG900

Length: 6500



Bi-Fold Stile Double Glazed

Length: 2800/6500



Mating Stile Double Glazed


Length: 6500



Lock Stile Double Glazed

DG900

Length: 6500



Rail

Double Glazed

DG904

Length: 6500

Windsor Bi-Fold Door Profiles





Wide Rail Double Glazed DG905 Length: 6500



44mm Mid rail Double GlazedDG912
Length: 6500



100mm Mid rail Double Glazed DG911 Length: 6500



Rail Bead Double Glazed CD318 Length: 6500



Meeting Stile Adapter CA436 Length: 4800



Edge Lock Kit Satin Chrome XPL508-SC



Edge Lock Kit Black XPL508-SB



Edge Lock Kit Pearl White XPL508-PW



Twin-Bolt Rod Kit P33096



1m Rod Extension Kit P84017



Twin-Bolt Lock Kit Black Non-Locking EDGE-KIT 1



Twin-Bolt Lock Kit Satin Chrome Non-Locking EDGE-KIT 2



Twin-Bolt Lock Kit Black Locking EDGE-KIT 3



Twin-Bolt Lock Kit Satin Chrome Locking EDGE-KIT 4



Twin-Bolt Lock Kit Black Non-Locking INTERLOCK-KIT 1



Twin-Bolt Lock Kit Satin Chrome Non-Locking INTERLOCK-KIT 2



250mm Flush Bolt Satin Chrome DN201-SC



250mm Flush Bolt Black DN201-BLK



Flush Bolt Guide FB7 Bag of 100



Sill Baffle PX0040 Roll of 300





Pivot Set Left Hand 93-101C



Pivot Set Right Hand 93-103C



Offset End Carrier Set **Left Hand** 93-291



Offset End Carrier Set Left Hand 93-293



Meeting Carrier Set 93-299



Intermediate Carrier Set 93-400



Offset Carrier Set Left Hand 93-491



Offset Carrier Set Right Hand 93-493



Hinge Handle Set Standard 93-320



Hinge Handle Set Offset 93-370



Hinge Set Standard 93-300



Hinge Set Offset 93-350



Standard Handle 93-321



Offset Handle 93-371




Centre Snubber 93-SN001



Bi-Fold Drilling Jig 93-DJ200



Standard Door Spigot CD218 Set of 4



Deep Pocket Door Spigot DS918 Set of 4



Hold Open Door Stop Black DN227



35mm Magnetic Catch MC100



12.5mm Magnetic Catch MC101



Q-Lon Door Stop Seal AQ21 Roll of 250m



Q-Lon Door Stop Seal with Backing QEZ48 Roll of 305m



Bi-Fold Stile Seal PX0648 Roll of 200m





Sill Gasket
Suit BF2
BFG100
Roll of 100 Pairs



Sill Gasket
Suit BF10/BF13/
BF14
BFG102
Roll of 250 Pairs



Wedge 5mm PF0774-4 Roll of 200m



Wedge 6mm PF0774-5 Roll of 200m



Wedge 24mm PX0084 Roll of 250m




Captive Wedge 24mm PX0646 Roll of 150m

Comet Sliding Door

Mid-Range Sliding Door





	— PERFORMANCE			
WERS				
U-Value	SHGC	TVW		
2.6 - 6.1	0.23 - 0.72	0.28 - 0.74		
N3 General / Corner				
Serviceability (+Pa)	Ultimate Pressure (+Pa)	Water Penetration (Pa)		
ир то 670	ир то 2000	ир то 250		

RW

23 - 30

Acoustic Ratings:

- **FEATURES**
- Frame: 50mm x 95mm
- Double Glazing: 18mm
- Single Glazing: 4mm 6.38mm
- 100kg stainless steel dual wheel rollers
- High quality face mounted d pull lock
- Sump sill drainage
- Optional security doors and tracks


Comet Sliding Door Profiles






High Performance Sill

HPS95 Length: 6500



Standard Sill CSD9


Length: 6500



Head

CSD1

Length: 6500



Jamb

CSD3


Length: 4900/6500



Threshold

CSD8

Length: 6500



S/G Male Stile

CSD5

Length: 4900/6500



S/G Interlock

CSD6


Length: 4900/6500



S/G Heavy Duty Interlock

STK4

Length: 4900/6500



3 Panel Adapter **Single Glazed**

STK10

Length: 2700



S/G Female Stile

STK7


Length: 6500



S/G Rail

CSD4

Length: 6500



D/G Male Stile

Length: 4900/6500



D/G Interlock

DGS97

Length: 4900/6500



D/G Heavy Duty Interlock


DGS80

Length: 4900/6500



D/G UHD Interlock

DGS100 Length: 4900



D/G 3 Panel **Adapter** DGS99

Length: 2700



D/G Female Stile

DGS82


Length: 6500



D/G UHD

Female Stile

DGS101 Length: 4900



D/G Rail

DGS81

Length: 6000



Corner Adapter Male


STK8

Length: 2700



Corner Adapter Female

STK9 Length: 2700



Door to Window Coupler


BC95

Length: 6000



Sill Support Bar 20mm x 1.6mm FB2016

Length: 4000



Ultra Heavy Duty S/G Interlock Style

STK14 Length: 4900



Ultra Heavy Duty S/G 4 Panel Adapter

STK17 Length: 4900

Comet Sliding Door Profiles





Gutter Sill Grate GS4 Length: 4000



145mm Gutter Sill GS95 Length: 6500



Fly door Track Bead GS5 Length: 6500



8mm Saddle Bead GS6 Length: 6500



Yarra View Edge Sliding Lock YARRAVIEW



Yarra View 4-Pin Cylinder YV-PIN CYLINDER



Yarra View Wafer Cylinder YV-WAFER CYLIN-DER



Yarra View
Dummy Handle
YV-DUMMYHANDLE



Yarra View
Dummy Plate
YV-DUMMY PLATE



Dummy Roller 3136 Box of 100 / or separately



40kg Single Wheel Roller8179
Box of 100 / or
separately



100kg Dual Wheel Roller 8358 Box of 100 / or separately



150kg Triple Wheel Roller 8387 Box of 50 / or separately



Bump Stop Suit HPS95 BS28 Bag of 100



Door Stop Black 1690-B Box of 100



Door Stop Satin Chrome 1690-C Box of 100



Fixing Block FB5 Bag of 350



Fixed Panel Fixing Block LB1 Bag of 500



Interlock Block LB4 Bag of 250





4.8mm x 5.5mm Wool Pile WP48550 Roll of 450m



4.8mm x 7.5mm Acoustic SealQL48750
Roll of 600m



Interlock End Cap Black / White / Grey EC60 Box of 400



UHD End Cap Suit DGS100 & DGS101 ECD70



27mm End Cap Suit STK7 / DGS82 ECD27MM Bag of 200



End Cap Suit STK4 ECD32MM Bag of 200



End Cap To Suit Comet Sliding Gutter Sill ECD95



Sill Baffle PX0040 Roll of 300m



Expansion Seal PX0049 Pack of 60m



Head Gasket GF95 Roll of 250 Pairs



Sill Gasket Suit HPS95GF97
Roll of 250 Pairs



Sill Gasket Suit CSD9 GF96 Roll of 250 Pairs



4mm Sliding Door Channel PF0742 Roll of 100m



5mm Sliding Door Channel PF0843 Roll of 100m




6mm Sliding Door Channel PF636 Roll of 100m




18mm D/G Channel PF0830 Roll of 150m

Comet Stacker Door

Mid-Range Stacker Door





residential zero threshold gutter sill.

PERFORMANCE -

U-Value

WERS

SHGC

TVW

2.8 - 6.2

0.22 - 0.68

0.22- 0.72

Exposure Condition: N3

Serviceability (+Pa)

> UP TO 800

Ultimate Pressure (+Pa)

> UP TO 1400

Water Penetration (Pa)

> UP TO 150

FEATURES ———

- Frame: 45mm x 103mm
- Double Glazing: 18mm
- Single Glazing: 4mm 6.38mm
- 100kg stainless steel dual rollers
- High Quality Face Mounted D Pull Lock
- Sump sill drainage
- Optional security doors and tracks

Comet Stacker Door Profiles





Sill with Flytrack

STK30


Length: 3700/6500



Standard Sill

STK2

Length: 3700/6500



Head

STK1

Length: 3700/6500



Jamb

STK3

Length: 4900/6500



Threshold

CSD8

Length: 6500



Flytrack Jamb/ Head

STK5

Length: 5500/6500



Door to Window Coupler

BC95


Length: 6000



Sill Support Bar 12mm x 3mm

FB123

Length: 3600



S/G Male Stile

CSD5


Length: 4900/6500



S/G Interlock

CSD6

Length: 4900/6500



S/G Heavy Duty Interlock

STK4


Length: 4900/6500



S/G Female Stile

STK7


Length: 6500



S/G Rail

CSD4

Length: 6500



D/G Male Stile

DGS96

Length: 4900/6500



D/G Interlock

DGS97

Length: 4900/6500



D/G Heavy Duty Interlock

DGS80

Length: 4900/6500



D/G UHD Interlock

DGS100 Length: 4900



D/G Female Stile

DGS82


Length: 6500



D/G UHD Female Stile

DGS101

Length: 4900



D/G Rail

DGS81

Length: 6000



Corner Adapter Male

STK8

Length: 2700



Corner Adapter Female

STK9

Length: 2700



Ultra Heavy Duty S/G Interlock Style

Length: 4900

STK14



Ultra Heavy Duty S/G 4 Panel Adapter

STK17

Length: 4900



8mm Saddle Bead

GS6

Length: 6500

Comet Stacker Door Profiles





Gutter Sill Grate GS4 Length: 4000



Gutter Sill Box Track GS8 Length: 6500



210mm Gutter Sill GS30 Length: 6500



Yarra View Edge Sliding Lock YARRAVIEW



Yarra View 4-Pin Cylinder YV-PIN CYLINDER



Yarra View Wafer Cylinder YV-WAFER CYLIN-DER



Yarra View
Dummy Handle
YV-DUMMYHANDLE



Yarra View
Dummy Plate
YV-DUMMY PLATE



Dummy Roller 3136 Box of 100 / or separately



40kg Single Wheel Roller8179
Box of 100 / or separately



100kg Dual Wheel Roller 8358 Box of 100 / or separately



150kg Triple Wheel Roller 8387 Box of 50 / or separately



Bump Stop Suit HPS95 BS28 Bag of 100



Door Stop Black 1690-B Box of 100



Door Stop Satin Chrome 1690-C Box of 100



Fixed Panel Fixing Block LB1 Bag of 500



Interlock Block LB4 Bag of 250



4.8mm x 5.5mm Wool PilePB48550
Roll of 450m





Interlock End Cap Black / White / Grey EC60 Box of 400



UHD End Cap Suit DGS100 & DGS101 ECD70



27mm End Cap Suit STK7 / DGS82 ECD27MM Bag of 200



End Cap Suit STK4 ECD32MM Bag of 200



End Cap To Suit Comet Stacker Gutter Sill ECD30



Sill Baffle PX0040 Roll of 300m



Expansion Seal PX0049 Pack of 60m



Head Gasket GF100 Roll of 250 Pairs



Sill Gasket GF101 Roll of 250 Pairs



Bumper Stop For Stacking Doors BS1



4mm Sliding Door Channel PF0742 Roll of 100m



5mm Sliding Door Channel PF0843 Roll of 100m




6mm Sliding Door Channel PF636 Roll of 100m



18mm D/G Channel PF0830 Roll of 150m

Artemis Series (12532CG)

Residential Complete Series



Artemis Series (12532CG) Frame with a sub sill

The Artemis Series is a stand alone complete series, which has the ability to create an Open In and Out Hinge Entry Door, Awning Window, Fixed Window, Sliding Window and Double Hung Window. The Artemis Series frame is commercial-grade with slimline panels to delivers strength while maintaining a streamlined appearance. Designed entirely for residential applications, this system was designed for the convenience of architects, and fabricators to complete projects with one series.

	— PERFORMANCE			
WERS				
U-Value	SHGC	TVW		
2.3 - 4.6	0.15 - 0.70	0.29 - 0.73		
Exposure Condition: N4				
Serviceability (+Pa)	Ultimate Pressure (+Pa)	Water Penetration (Pa)		
ир то 800	ир то 2000	ир то 200		

FEATURES —

• Frame: 22.5 or 32mm x 125mm

• Double Glazing: 24mm - 32mm

• Single Glazing: 4mm - 10.5mm

• Stand alone system

Square cut frame


Adapted Fly door

 Timber door panels in standard sizes for Hinge Door Configurations

• Optional sub sills available


Artemis Series: Hinge Door Profiles






Titan Entry Door Frame DJ125

125 x 32 Length: 6000




Titan Entry Door Jamb DJ129

125 x 22.5 Length: 6000



Titan Entry Door Hook Hinge Frame

DJ130 Length: 6000



Titan Entry Door Sill

DJ126

Length: 6000



Titan Entry Door Double Glazing Bead

DJ128

To suit DJ127 Length: 6000



Double to Single Glazing Bead DJ127


To suit DJ127 Length: 6000



135mm Threshold

DJ135

Length: 6000



44mm Door Stop

DJ132

To suit DJ125 + **DJ129**

Length: 6000




40mm Timber Door Stop Reducer

DJ133

To suit DJ132

Length: 6000



Frame Coupler

DJ134

To suit DJ125 + **DJ129**

Length: 6000



D/Glazed to S/ **Glazed Pocket Adapter**


DF610 Length: 6500



S/Glazed Pocket

Insert **DF606**

Length: 6500



Sub Sill

SS12

125mm Titan **System**

Length: 6500



D/Glazed Pocket

Filler

DF605

Length: 6500



Sash Stop

DJ131

Length: 6500



Lock Stile Single Glazed CD213

Length: 6500



Hinge Stile Single Glazed CD214


Length: 6500



Mating Stile Single Glazed

BF5


Length: 6500



S/G Door Rebate Style

CD240

Length: 6000



Wide Lock Stile Single Glazed

CD300

Length: 6500




Wide Hinge Stile Single Glazed CD301

Length: 6500



Rail Single Glazed

CD200 Length: 6500




Wide Rail Single Glazed

CD201 Length: 6500



Mid rail Single Glazed

CD203 Length: 6500



Mid rail **Single Glazed**

CD204 Length: 6500

Artemis Series: Hinge Door Profiles






Rail Bead Single Glazed CD202 Length: 6500



Meeting Stile Adapter CA436 Length: 4800



Single Glazed Reducer CD221 Length: 6500



200mm SG Mid rail CD320 Length: 6500



Lock Stile Deep Pocket DG920 Length: 6500




D/G Hinge Stile **Deep Pocket** DG921 Length: 6500




D/G Rebate Face Wide Style DG960 Length: 6500




D/G Deep Pocket **Rebate Style** DG940 Length: 6500



Mating Stile Deep Pocket DG922 Length: 6500




Wide Lock Stile **Deep Pocket** DG930 Length: 6500




Wide Hinge Stile **Deep Pocket** DG931


Length: 6500



Lock Stile Double Glazed DG900 Length: 6500




Hinge Stile Double Glazed DG902 Length: 6500



Mating Stile Double Glazed


Length: 6500




Wide Lock Stile **Double Glazed** DG910 Length: 6500




Wide Hinge Stile Double Glazed DG906 Length: 6500



Rail **Double Glazed** DG904 Length: 6500



Wide Rail **Double Glazed** DG905 Length: 6500



100mm Mid rail **Double Glazed** DG911 Length: 6500



Rail Bead Double Glazed CD318 Length: 6500



44mm Mid rail **Double Glazed** DG912





Edge Lock Kit Satin Chrome XPL508-SC



Edge Lock Kit Black XPL508-SB



Edge Lock Kit Pearl White XPL508-PW



Twin-Bolt Rod Kit P33096



1m Rod Extension Kit P84017



250mm Flush Bolt Satin Chrome DN201-SC



250mm Flush Bolt Black DN201-BLK




Fast Fix Hinge Clear Anodised AH130CAN




Fast Fix Hinge White AH130WH



Fast Fix Hinge Black AH130BLK



Standard Door Spigot CD218 Set of 4



Deep Pocket Door Spigot DS918 Set of 4



Flush Bolt Guide FB1 Bag of 200



Flush Bolt Ferrule Black DN205



Aquamac Bi-Fold Seal AQ21 Roll of 250m



Sub Sill End Cap ECD12 To suit SS12



Frame Gasket GF125 To suit DJ125 + DJ129



Titan Entry Gasket GF135 To suit DJ135



Titan Entry Gasket GF126 To suit DJ127



Sill Baffle PX0040 Roll of 300



WP69500 3mm x 13mmPS13
Roll of 450m



Weep Hole Cover WHC1239 Bag of 100



Apartment Door End Cap EC25 50 left / 50 right



Wedge 5mm PF0774-4 Roll of 200m



Wedge 6mm PF0774-5 Roll of 200m








Roll of 150m

Titan Built-In-Flytrack-Track (BIF) Apartment Door

High-End Apartment Door



The Built-in Fly track (BIF) Apartment Door is a high-performing system designed for top-of-the-range contemporary homes. As a commercial-grade system with 2-track or 3-track options, it delivers exceptional durability while creating large openings without taking up extra space. Complemented by premium hardware, the BIF Apartment Door is a standout feature that elevates the value and durability of any project.

———— PERFORMANCE ———— FEATURES ———

WERS

U-Value	SHGC	TVW
2.7 - 6.1	0.17 - 0.62	0.21 - 0.68

Exposure Condition: N5

Serviceability (+Pa)	Ultimate Pressure (+Pa)	Water Penetration (Pa)
UP TO	UP TO	UP TO
1200	4000	360


Acoustic Ratings: RW

27 - 36

- Frame: 100mm / 150mm x 55mm
- Double Glazing: 24mm
- Single Glazing: 4mm 6.38mm
- Integrates with the 10055-DG Centre Glazed System
- 150kg triple wheel stainless steel bearing rollers
- Evolution hardware
- Sump sill drainage
- A range of stiles available
- Sub framing available

Titan BIF Apartment Door Profiles





2 Track Head CAD169 Length: 4500/6500



3 Track Head CAD170 Length: 4500/6500



2 Track Sill CAD167 Length: 4500/6500



3 Track Sill CAD168 Length: 4500/6500



2 Track Jamb CAD161 Length: 5000/6500



3 Track JambCAD119
Length: 5000/6500



Threshold/Cover CAD138 Length: 6500



Single Flytrack Jamb CAD171 Length: 6500



Double Flytrack Jamb CAD172 Length: 6500




Pocket Filler Suit Flytrack Jambs CA305 Length: 3600




90mm Frame Filler CA102 Length: 6500



Female/Lock Stile Suit Evolution Lock CAD157 Length: 6500



58mm Lock Stile CAD150 Length: 5000/6500



76mm Lock Stile CAD152 Length: 6500




Wide Lock Stile CAD146 Length: 6500



Male Stile CAD156 Length: 6500




Interlock CAD151 Length: 5000/6500



Wide Interlock CAD148 Length: 6500



Heavy Duty Interlock CAD124 Length: 6500




3 Panel Adapter CAD018 Length: 3000



Beveled Rail Single Glazed CAD005 Length: 6500



Beaded Rail Single Glazed CAD114 Length: 6500



Wide Beaded Rail Single Glazed CAD143 Length: 6500




Rail CAD118 Length: 6500




Boxed Rail CAD025 Length: 6500

Titan BIF Apartment Door Profiles







Boxed Beaded Rail CAD026 Length: 6500



Heavy Duty Rail Suit 8173 Rollers CAD142 Length: 6500



Wide Sill CAD142 Length: 6500



Wide Beaded Rail CAD144 Length: 6500



S/G Rail Bead CAD115 Length: 6500




D/G Rail Bead CAD127 Length: 6500




S/G Reducer CAD164 Length: 6500




Mid rail CAD120 Length: 6500



2 Track **Reveal Adapter** CA490 Length: 6500



Ezy Reveal Adapter CA450 Length: 6500



Ezy Reveal Adapt-CA493 Length: 6500



3 Track **Reveal Adapter** CAD019

Length: 6500



FB2516 Length: 4000



Evolution Lock Kit Black D-Handles EVOLUTION-KIT#1



Evolution Lock Kit Black Flush handles **EVOLUTION-KIT#2**



Evolution Lock Kit S/S Flush handles **EVOLUTION-KIT#3**



Evolution Lock Kit Painted D-handles EVOLUTION-KIT#4



Evolution Lock Kit Painted Flush Handles **EVOLUTION-KIT#5**





Yarra View Edge **Sliding Lock YARRAVIEW**



Yarra View 4-Pin Cylinder YV-PIN CYLINDER



Yarra View Wafer Cylinder YV-WAFER CYLIN-DER



Yarra View **Dummy Handle** YV-DUMMYHAN-DLE



Yarra View **Dummy Plate** YV-DUMMY PLATE



Dummy Roller 3136 Box of 100 / or separately



100kg Dual Wheel Roller 8358 Box of 100 / or separately



150kg Triple **Wheel Roller** 8387 Box of 50 / or separately



150kg Dual Wheel Roller Suit CAD026 Rail 8173 Box of 50 / or separately



200kg 5-Wheel Roller 8275 Box of 50



Bump Stop Suit HPS95 **BS28** Bag of 100



Door Stop Black 1690-B Box of 100



Door Stop Satin Chrome 1690-C Box of 100



Fixing Block FB6 Box of 200



Apartment Door End Cap EC25 50 left / 50 right




10mm Square **Block** LB2 Box of 1000



6.9mm x 5.0mm **Wool Pile** WP69500 Roll of 400m



6.9mm x 6.5mm **Acoustic Seal** QL69650 Roll of 600m



Heavy Duty Interlock End Cap ECD124



10mm Hole Plug HP10 Bag of 200



Sill Baffle PX0040 Roll of 300m



Anti Binding Rubber PF0630 Roll of 100m



2 Track Sill Gasket **ADG120** Roll of 100 Pairs



3 Track Sill Gasket ADG200 Roll of 100 Pairs





door interlock end cap - pairs L & R LB5-R and LB5-L





Bumper Stop For Stacking Doors BS1



4mm Channel Sliding Door Channel PF0742 Roll of 100m



5mm Channel Sliding Door Channel PF0843 Roll of 100m



6mm Channel Sliding Door Channel PF636 Roll of 100m



24.76mm D/G ChannelPF0551
Roll of 50m











17 Broadfield Rd Broadmeadows VIC 3047

03 9357 2888

www.conceptaluminium.com.au

