

# Comet Sliding Door.



The Comet Sliding Door is a versatile system available in 2, 3, or 4-panel configurations, accommodating both large and small openings. It is commonly used in bedrooms, living rooms, backyard entries, and laundries, providing increased ventilation and natural light without taking up additional space. The Comet Sliding Door pairs seamlessly with other 90mm frame windows and doors to create custom combinations, and when used with our residential zero-threshold gutter sill, it delivers a smooth, step-free transition that complies with accessibility requirements.



## Features & Benefits

- Uses a built-in drainage sump ensures effective water management, protecting your home from leaks and extending the door's lifespan
- Uses 100kg Stainless steel ball bearing rollers for smooth, durable operation
- Equipped with a built-in fly track to keep intruders out while maintaining a clean, unobtrusive appearance
- Compatible with corner designs, allowing flexible layouts and creative design possibilities for modern homes
- Use a high-quality Face Mounted D Pull Lock with optional colour coating

### Maximum Sizes Recommended

Sash Height	2035mm
Total Height	2400mm
Rail Width	1200mm
Sash Weight	180kg

### Frame Dimensions

Height	50mm
Depth	95mm

### Glazing Capacity

Single Glazing	4mm – 6.38mm
Double Glazing	18mm

### Min - Max Energy Performance

U-Value	2.6 - 6.1
SHGC	0.23 - 0.72
TVW	0.28 - 0.74

View our full list of WER's rating at [conceptaluminium.com.au](http://conceptaluminium.com.au)

### Maximum Performance

Serviceability (+Pa)	800
Ultimate Pressure (+Pa)	2000
Water Penetration (Pa)	200
Acoustic Rating (RW)	23 - 30
Exposure Condition	N3

## Configurations

